



MUSTANG M3 CS



PHOTO SOON



alu 6061X-lite



17" / 19" / 21"



20 speed

MUSTANG M3 CS

Technical data

WHEEL SIZE / FRAME	29" / alu 6061 X-lite	RIMS	aluminium doublewall
SIZE	M – 17" / L – 19" / XL – 21"	FRONT HUB	Shimano HB-TX505
FORK	Suntour XCM RL 100mm	REAR HUB	Shimano FH-TX505
DAMPER	—	CASSETTE	Shimano CS-LG400-10 11-39T 10 speed
DRIVETRAIN	2×10	HANDLEBAR	Romet aluminium 720mm/31,8mm
FRONT SHIFTERS	Shimano Cues SL-U6000 2 speed	STEM	Romet aluminium 90mm/31,8mm
REAR SHIFTERS	Shimano Cues SL-U6000-10R 10 speed	SEAT POST	Romet aluminium 31,6mm/350mm
FRONT DERAILLEUR	Shimano Cues FD-U4000	GRIPS	Brat Trefl 130mm
REAR DERAILLEUR	Shimano Cues RD-U6020-10 SGS	SADDLE	Romet
CRANKSET	Shimano Cues FC-U6000-2 36-22T, 170mm	PEDALS	FP-971 aluminium
FRONT BRAKE	Shimano BL-MT200/BR-M200	FRONT LAMP	—
REAR BRAKE	Shimano BL-MT200/BR-M200	REAR LAMP	—
FRONT BRAKE DISC	Shimano SM-RT10 centerlock 160mm	WEIGHT	—
REAR BRAKE DISC	Shimano SM-RT10 centerlock 160 mm	COLOURS	dark blue-yellow
TYRES	Michelin Country Grip'R 29"×2,1"		

Geometry

	M	L	XL
Tyre size	29"	29"	29"
A - frame size	432 mm	485 mm	535 mm
B - top tube length	610 mm	630 mm	640 mm
C - chainstay length	435 mm	435 mm	435 mm
D - seat tube angle	69°	69°	69°
E - head tube angle	70°	69°	69°
F - wheel base	1100 mm	1130 mm	1141,5 mm
G - head tube length	110 mm	110 mm	125 mm
H - fork length	495 mm	495 mm	495 mm
Stack	—	—	—
Reach	—	—	—
Standover height	—	—	—
Maximum tyre size	2,25"	2,25"	2,25"

