

CROSS

— S —  
ORKAN 5 C S D



turquoise  
-lime green



white  
-champagne



28"



alu 6061



18" / 20"



18 speed



15,8 kg

## ORKAN 5 CSD

## Technical data

WHEEL SIZE / FRAME	28" / alu 6061	RIMS	aluminium doublewall
SIZE	M – 18" / L – 20"	FRONT HUB	Shimano HB-TX505
FORK	Suntour NEX E-25 NLO 75mm tapered	REAR HUB	Shimano FH-TX505
DAMPER	—	CASSETTE	Shimano CS-LG300-9,11-36T 9 speed
DRIVETRAIN	2×9	HANDLEBAR	RMT Components aluminium 680mm/31,8mm
FRONT SHIFTERS	Shimano Cues SL-U4000 2 speed	STEM	RMT Comp. adj. 85mm Internal cable routing
REAR SHIFTERS	Shimano Cues SL-U4010-9R 9 speed	SEAT POST	RMT components 27,2mm/350mm
FRONT DERAILLEUR	Shimano Cues FD-U4010	GRIPS	Wittkop Medicus Sport
REAR DERAILLEUR	Shimano Cues RD-U4020 SGS	SADDLE	Selle Royal Ariel 8058 DR
CRANKSET	Shimano Cues FC-U4010-2, 46-30T, 170mm	PEDALS	FP-920B
FRONT BRAKE	Shimano BL-MT200/BR-M200	FRONT LAMP	—
REAR BRAKE	Shimano BL-MT200/BR-M200	REAR LAMP	—
FRONT BRAKE DISC	Shimano SM-RT10 centerlock 160mm	WEIGHT	15,8 kg
REAR BRAKE DISC	Shimano SM-RT10 centerlock 160mm	COLOURS	white-champagne, turquoise-lime green
TYRES	VeeTire Speedster 700×44C		

## Geometry

	M	L
Tyre size	28"	28"
A - frame size	460 mm	510 mm
B - top tube length	566 mm	580 mm
C - chainstay length	460 mm	460 mm
D - seat tube angle	68°	68°
E - head tube angle	71°	71°
F - wheel base	1069 mm	1083 mm
G - head tube length	145 mm	165 mm
H - fork length	450 mm	450 mm
Stack	613 mm	632 mm
Reach	384,5 mm	392 mm
Standover height	—	—
Maximum tyre size	1,75"	1,75"

