

— S —
ORKAN 5 M



navy blue
-blue-silver



silver
-graphite-copper



ORKAN 5M

Technical data

WHEEL SIZE / FRAME	28" / alu 6061	RIMS	aluminium doublewall
SIZE	M – 19" / L – 21"	FRONT HUB	Shimano HB-TX505
FORK	Suntour NEX HLO 63mm	REAR HUB	Shimano FH-TX505
DAMPER	—	CASSETTE	Shimano CS-HG201 11-32T 9 speed
DRIVETRAIN	3×9	HANDLEBAR	aluminium 680mm/15°/31,8mm
FRONT SHIFTERS	Shimano Altus SL-M2010 3 speed	STEM	adjustable TDS-D299 N-8 31,8mm/105mm
REAR SHIFTERS	Shimano Altus SL-M2010 9 speed	SEAT POST	aluminium 30,9mm 350mm
FRONT DERAILLEUR	Shimano Altus FD-M370	GRIPS	Brat Kier 138mm
REAR DERAILLEUR	Shimano Alivio RD-T4000	SADDLE	Selle Royal
CRANKSET	Shimano FC-M371 48/36/26T 170mm	PEDALS	FP-920B aluminium
FRONT BRAKE	Shimano BL-MT200/BR-MT200	FRONT LAMP	—
REAR BRAKE	Shimano BL-MT200/BR-MT200	REAR LAMP	—
FRONT BRAKE DISC	Shimano SM-RT10 centerlock 160mm	WEIGHT	14,8 kg
REAR BRAKE DISC	Shimano SM-RT10 centerlock 160mm	COLOURS	navy blue-blue-silver, silver-graphite-copper
TYRES	VeeTire Speedster 700×44C		

Geometry

	M	L
Tyre size	28"	28"
A - frame size	483 mm	533 mm
B - top tube length	570 mm	580 mm
C - chainstay length	460 mm	460 mm
D - seat tube angle	66°	66°
E - head tube angle	71°	71°
F - wheel base	1073 mm	1083 mm
G - head tube length	150 mm	150 mm
H - fork length	450 mm	450 mm
Stack	—	—
Reach	—	—
Standover height	—	—
Maximum tyre size	1,75"	1,75"

