



E-MODECO SUV 1.0

504Wh



gray-silver



gold-black



lime green



Bafang G020



250W 45Nm



504Wh



9 speed

E-MODECO SUV 1.0 504Wh

Technical data

MOTOR / PERFORMANCE	Bafang G020 rear wheel, 250 Watt, 45Nm speed sensor	TYRES	VeeTire Mission 29×2.1
CONTROL UNIT	display Bafang DP C220 CAN	RIMS	aluminium doublewall RMT Components
BATTERY	504Wh	FRONT HUB	aluminium
CHARGER	2A	REAR HUB	—
WHEEL SIZE / FRAME	29" / alu 6061	CASSETTE	Shimano Cues CS-LG300-9, 11-41T, 9 speed
SIZE	M – 17" / L – 19"	HANDLEBAR	RMT Comp. alu. 660mm/680mm, 31,8mm
FORK	Suntour NEX-E25-LO-DS 75mm	STEM	RMT alu. adj. 85mm/105mm Int. cable rout. 31,8mm
DAMPER	—	SEAT POST	aluminium suspension 30,9mm/300mm
DRIVETRAIN	1×9	GRIPS	Wittkop Medicus Sport
FRONT SHIFTERS	—	SADDLE	Selle Royal Vivo
REAR SHIFTERS	Shimano Cues SL-U4010 9 speed	PEDALS	FP-803
FRONT DERAILLEUR	—	FRONT LAMP	Satelite C13
REAR DERAILLEUR	Shimano Cues RD U4000	REAR LAMP	Buchel Edge
CRANKSET	Prowheel 38T 170mm	WEIGHT	24,6 kg
FRONT BRAKE	Shimano BL-MT200 hydraulic	COLOURS	gray-silver, gold-black, lime green
REAR BRAKE	Shimano BL-MT200 hydraulic		
FRONT BRAKE DISC	180mm		
REAR BRAKE DISC	160mm		

Geometry

	M	L
Tyre size	28"	28"
A - frame size	432 mm	483 mm
B - top tube length	588 mm	613 mm
C - chainstay length	460 mm	460 mm
D - seat tube angle	73°	73°
E - head tube angle	70°	70°
F - wheel base	1110 mm	1125 mm
G - head tube length	160 mm	160 mm
H - fork length	489 mm	489 mm
Stack	656 mm	656 mm
Reach	383 mm	408 mm
Standover height	415 mm	415 mm
Maximum tyre size	2.00"	2.00"

