



E-MODECO TRK 1.0

504Wh



● red ○ white ● graphite



Bafang G020



250W 45Nm



504Wh



8 speed

E-MODECO TRK 1.0 504Wh

Technical data

MOTOR / PERFORMANCE	Bafang G020 rear wheel, 250 Watt, 45Nm speed sensor	TYRES	VeeTire Zilent 700×47C
CONTROL UNIT	display Bafang DP C220 CAN	RIMS	aluminium doublewall RMT Components
BATTERY	504Wh	FRONT HUB	aluminium
CHARGER	2A	REAR HUB	—
WHEEL SIZE / FRAME	29" / alu 6061	CASSETTE	Shimano HG31-8, 11-34T, 8 speed
SIZE	M – 17" / L – 19"	HANDLEBAR	RMT Comp. alu. 660mm, 31,8mm
FORK	Suntour NEX-E25-LO-DS, 75mm, tapered	STEM	RMT alu. adj. 85mm/105mm Int. cable rout. 31,8mm
DAMPER	—	SEAT POST	aluminium suspension 30,9mm/300mm
DRIVETRAIN	1×8	GRIPS	Wittkop Medicus Ergo
FRONT SHIFTERS	—	SADDLE	Selle Royal Essenza
REAR SHIFTERS	Shimano SL-M315-8R 8 speed	PEDALS	FP-872ZU
FRONT DERAILLEUR	—	FRONT LAMP	Satelite C9
REAR DERAILLEUR	Shimano Acera RDM3020-8	REAR LAMP	Buchel Edge
CRANKSET	Prowheel 38T 170mm	WEIGHT	24,8 kg
FRONT BRAKE	Shimano BL-MT200 hydraulic	COLOURS	white, graphite, red
REAR BRAKE	Shimano BL-MT200 hydraulic		
FRONT BRAKE DISC	160mm		
REAR BRAKE DISC	160mm		

Geometry

	M	L
Tyre size	28"	28"
A - frame size	432 mm	483 mm
B - top tube length	588 mm	613 mm
C - chainstay length	460 mm	460 mm
D - seat tube angle	73°	73°
E - head tube angle	70°	70°
F - wheel base	1110 mm	1125 mm
G - head tube length	160 mm	160 mm
H - fork length	489 mm	489 mm
Stack	656 mm	656 mm
Reach	383 mm	408 mm
Standover height	415 mm	415 mm
Maximum tyre size	2.00"	2.00"

